

HIGHTEC FORM NMU 150

Multi-functional product for cold forming of large parts

Description

HIGHTEC FORM NMU 150 is a water-immiscible, chlorine-free, mineral oil-based, multi-functional oil. Due to the high polarity of the substances, it is particularly suitable for use as both a slide way and cold extrusion oil at the same time.

Application

HIGHTEC FORM NMU 150 is easy to apply. It can be applied onto the workpiece to be machined by spraying, flow coating, immersion or rolling.

Advantages

- Versatile metal forming lubricant, also suitable as a bed way lubricant
- High lubricating performance
- High level of wear protection for the tools
- Very good compatibility with all tool coatings
- Good corrosion protection properties

Recommendation

Field of application: - Cold extrusion and slide way - Deep drawing, pressing, punching HIGHTEC FORM NMU 150 is suitable for machining steel, stainless steel, aluminium and non-ferrous metals.

Notes

- Storage:
- When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 36 months
- Temperature range: 0-40°C
-
- Degreasing:
- HIGHTEC FORM NMU 150 can be degreased using conventional
- degreasing media, for example by spray cleaning or
- immersion cleaning in aqueous-alkaline cleaning agents.



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.9
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	150-160
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	>180

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

